

for each physical disk unit, and

control means for accessing one of said plurality of physical disk units which stores the designated logical volume, in accordance with said number of operations,

wherein said control means compares numbers of operations corresponding to a plurality of physical disk units which store said designated logical volume with each other, selects the single physical disk unit which has a minimum number of operations based on the comparison, and outputs a request to the single minimum waiting physical disk unit,

wherein said control means increments the number of operations of said selected physical disk unit in accordance with a request for said operation and decrements the number of operations of a physical disk unit whose operation has been completed, in accordance with an end of said operation,

wherein each of said physical disk units performs requested operations in a queued order, and

wherein said memory stores a table indicating a correspondence of the plurality of physical disk units and said designated logical volume; and said control means refers to said memory with said designated logical volume to select said single physical disk unit on which said designated logical volume is allocated in accordance with said designation of said designated logical volume by a high-rank apparatus.

Sub #1
3. ~~(AS TWICE AMENDED) The RAID apparatus according to claim 1, wherein said control means includes:~~

a channel adapter circuit performing interface control with said high-rank apparatus;

F2
a device adapter circuit accessing said physical disk units in accordance with a requested operation; and

a resource manager circuit determining one of the plurality of physical disk units to be accessed in accordance with said number of operations in said memory in response to a transfer request from said channel adapter circuit, and requesting said device adapter circuit to perform an operation accessing said determined physical disk unit.

4. ~~(as TWICE AMENDED) The RAID apparatus according to claim 3, wherein said~~

resource manager circuit increments a number of operations of said selected physical disk unit in accordance with the request for said operation and decrements the number of operations of the physical disk unit whose operation has been completed, in accordance with the end of said operation of said device adapter circuit.

~~5. (AS ONCE AMENDED) The RAID apparatus according to claim 3, wherein said memory stores status information indicating statuses of said physical disk units; and said resource manager circuit refers to said status information to determine whether those physical disk units which store said designated logical volume are normal and selects a normal physical disk unit.~~

~~7. (as FIVE TIMES AMENDED) An access control method for a RAID apparatus comprising a plurality of physical disk units storing a plurality of copies of each of logical volumes, and a disk controller accessing any physical disk unit which stores a designated logical volume to thereby access said designated logical volume, said method comprising:~~

~~determining a plurality of physical disk units which store a designated logical volume;~~

~~and~~

~~selecting one of said determined physical disk units in accordance with the number of operations requested to said physical disk units, said selecting comprising:~~

~~comparing said numbers of operations of a plurality of physical disk units which store said designated logical volumes with each other,~~

~~accessing the single physical disk unit which has a minimum number of operations based on the comparison and outputting a request to said single minimum waiting physical disk unit,~~

~~incrementing the number of operations of said accessed physical disk unit in accordance with a request for said operation, and~~

~~decrementing the number of operations of a physical disk unit whose operation has been completed, in accordance with an end of said operation,~~

~~wherein each of said plurality of physical disk units performs requested operations in a queued order, and~~

43 ~~Contd~~

wherein said selecting further comprises referring to a memory storing a table indicating a correspondence of the plurality of physical disk units and said designated logical volume to select a physical disk unit on which said designated logical volume is allocated in accordance with said designation of said designated logical volume by a high-rank apparatus.

44

~~9. (AS THREE AMENDED) The access control method according to claim 7, wherein~~
said determining step determines said plurality of physical disk units in response to a transfer request from said high-rank apparatus; and

said selecting includes:

requesting an operation for accessing said physical disk unit determined in accordance with said number of operations, and

~~accessing said physical disk unit in accordance with said requested operation.~~

45

10. (AS TWICE AMENDED) The access control method according to claim 9, wherein the number of operations of said determined physical disk unit is stored in said memory, and a memory location at which the number of operations is stored is incremented in accordance with the request for said operation and is decremented in accordance with the number of operations of the physical disk unit whose operation has been completed, in accordance with an end of said operation of said physical disk unit.

46

~~11. (AS TWICE AMENDED) The access control method according to claim 7, wherein~~
said selecting includes:

referring to status information to determine indicative of statuses of said physical disk units, stored in said memory, to determine whether those physical disk units which form said designated logical volume are normal; and

~~selecting a normal physical disk unit.~~

47 500

13. (as FIVE TIMES AMENDED) A RAID apparatus comprising:

physical disk units storing redundant logical volumes, a first of the redundant logical

volumes being stored on one of the physical disk units, and a second of the redundant logical volumes being stored on another of the physical disk units; and

17 *Handwritten*
a disk controller counting numbers of operations respectively requested of each of the physical disk units and accessing one of the first and the second of the redundant logical volumes based on a minimum number of the numbers of operation respectively requested of each of the physical disk units based on the counting, and outputs a request to the single minimum waiting physical disk unit,

wherein said disk controller increments the number of operations of an accessed physical disk unit in accordance with a request for said operation and decrements the number of operations of an accessed physical disk unit whose operation has been completed, in accordance with an end of said operation,

wherein each of said physical disk units performs requested operations in a queued order, and

wherein said disk controller refers to a table indicating a correspondence of the plurality of physical disk units and said redundant logical volumes to select the accessed single physical disk unit on which one of said redundant logical volumes is allocated in accordance with said designation of said one of said redundant logical volumes by a high-rank apparatus.

14. (as FOUR TIMES AMENDED) A RAID controller accessing one of a plurality of physical disk units storing a plurality of copies of each of logical volumes to thereby access a designated logical volume, comprising:

18 *Handwritten*
a memory storing a number of operations requested to each physical disk unit corresponding to each physical disk unit; and

a controller comparing said numbers of operations corresponding to a plurality of physical disk units which store said designated logical volume with each other, and selecting single one of said plurality of physical disk units which has a minimum number of operations based on the comparison and outputting a request to said single minimum waiting physical disk unit,

wherein said controller increments the number of operations of said selected physical disk unit in accordance with a request for said operation and decrements the number of operations of a physical disk unit whose operation has been completed, in accordance with an

end of said operation, wherein each of said plurality of physical disk units performs requested operations in a queued order, and

wherein said memory stores a table indicating a correspondence of the plurality of physical disk units and said designated logical volume; and said controller refers to said memory with said designated logical volume to select a physical disk unit on which said designated logical volume is allocated in accordance with said designation of said designated logical volume by a high-rank apparatus.

15. (as FOUR TIMES AMENDED) A balancing access method for a RAID apparatus comprising a plurality of physical disk units storing a plurality of copies of each of logical volumes, comprising:

comparing numbers of operations of a plurality of physical disk units which store a designated logical volume with each other;

selecting single one of said physical disk units which has a minimum number of operations based on the comparison and outputting a request to said single minimum waiting physical disk unit;

incrementing the number of operations of said accessed physical disk unit in accordance with a request on said operation; and

decrementing the number of operations of a physical disk unit whose operation has been completed, in accordance with an end of said operation, wherein each of said physical disk units performs requested operations in a queued order, and

wherein said selecting further comprises referring to a memory storing a table indicating a correspondence of the plurality of physical disk units and said designated logical volume to select said single physical disk unit on which said designated logical volume is allocated in accordance with said designation of said designated logical volume by a high-rank apparatus, and wherein said balancing access method auto-adjusts loads between the physical disk units.

16. (as FOUR TIMES AMENDED) A storage medium of a RAID apparatus storing a program, said program which when executed by a computer causes the computer to execute processes comprising: